

UNIVERSAL

CHILLING SYSTEMS

UCS-5W WATER COOLED CHILLER PHYSICAL DATA

Cooling Capacity	kcal/h		15100
	BTU/h		60000
	Nominal Tonnage.	RT	5
	Outlet Water Temp.	°F	50
	Condensation Temp.	°F	104
Power Supply			3PH-460V-60HZ
Max Amp		A	11
Total Power Input		HP	7
Power Supply Cable Diameter			AWG 12
Safety Protection Device			Overload, Inverse Phase, High/Low Pressure, Water Flow, Water Level & Anti-Freeze Protection
Refrigerant	Type		R410A
	Charge	Lbs	9.9
Compressor	Start Mode		Direct start
	Type		Scroll Type
	Qty		1
	HP		6
	RLA (Rated Load Amp)		11.8
	LRA(Locked Rotor Amp)		62
Condenser	Type		tube and shell
	Subcooling	°F	9
	Heat Rejection	BTU/h	80535
	Cooling Water Flow	GPM	17
	Water Pressure Drop	PSI	7
Evaporator	Type		tube and shell
	Superheat	°F	9
	Heat Rejection	BTU/h	60,060
	Chilled Water Flow	GPM	13
	Water Pressure Drop	PSI	5
Energy Adjust Mode			100%-0%
Throttling Device	Mode		thermal expansion valve
Pipe	Chilled Water Inlet/Outlet		MNPT 1"
	Cooling Water Inlet/Outlet		MNPT 1"
Water Pump	Flow	GPM	13
	Head	PSI	55.1
	LRA	A	7.2
	Power	HP	1.0
Water Tank	Capacity	GAL	18
Sound Pressure	DBA		65

UNIVERSAL

CHILLING SYSTEMS

Programming Controller	Display	LCD display
	Controller	microcomputer controller
	Temp Control Range °F	41°F ~95°F
	Temp Control Accuracy°F	±3.6°F
Dimensions	inches (LxWxH) (For Reference)	51x24x57
Weight	lbs (For Reference)	397

NOTES:

- 1 Cooling tons based on 10°C(50°F) chilled water outlet and 30°C(86°F) cooling water inlet.
Chilled water work allowed temperature range: 5°C~35°C(41°F ~95°F).
- 2 Chilled water in and out temperature difference: 3°C~8°C(5.4°F~14.4°F);
Allowed ambient temperature range: -20°C~40°C(-4°F~104°F).
- 3 Power supply: 3PH-460V-60HZ , Allowing the voltage fluctuate ±10%,
allow phase voltage difference ±2%, Allow the frequency range ±0.2Hz.